



UNIQUE
IN NDT

PILOT+

162 dB acquired at once
No more analog gain!
Full Parallel 8 channels
Designed for IP 67 Bipolar, Burst & AWG Optional



PULSER

Pulser Type 1	8 Pulsers up to 400 V (Negative Square)
Pulser Type 2	8 Pulsers Bipolar ± 100 V (AWG in option: burst, gaussian, chirp)
Pulse Width	30 to 1000 ns
Pulse Width Resolution	4 ns
Maximum PRF	20 kHz (higher option)

RECEIVER

Receiver #	8 parallel channels
Receiver Resolution	27 bits (no analog gain required)
Receiver Gain Range	162 dB at once
Receiver Bandwidth	0.3 to 20 MHz (50 kHz in option)
Receiver Input	± 10 V

SIGNAL PROCESSING

FIR Filter	Up to 32 taps
Different Filter per Cycle	Choose from 15 user defined filters
Ascan Resolution	8, 16, 27 bits, linear and log scale
Ascan Sampling	100 MHz
Decimation	50, 33, 25, 20, 16.67, 14.28, 12.50, ... MHz
Ascan Compression	Yes
Acquire All Ascans	Yes
Ascan Length	Up to 32 k points
Gates	4 (Amplitude, TOF)
Gate Modes	Any (Peak, Flank, Zero before crossing, Zero after crossing)
IF Gate and Ascan	Yes, no limitations

COMMUNICATION

Communication Link	LAN 1 Gb (TCP/IP)
Useful UT Data Flow ⁽¹⁾	100 MB/s

SYSTEM

Configurations	8 parallel channels per unit
Channel Mode	Full Parallel and Multiplexed
UT Modes	Pulse/Echo, Pitch & Catch, Through Transmission (TT)
Dimensions	240 x 140 x 45 mm 9.45 x 5.51 x 1.77 in.
Weights	< 1.5 Kg / 3.3 lb
Mechanical Integration	Bracket Plate in option
IP Rating	Designed for IP 67
Power Consumption ⁽²⁾	10 W
Temperature Monitoring	Yes
Open Source SDK	Yes (Fully Documented API)
Software Languages	C++, Python, C#, LabVIEW, MATLAB, etc...
Operating Systems	Windows, Linux
Multiplatform Compatibility	With all AOS products

I/O MANAGEMENT

Encoders	X, Y (differential, single ended)
Encoder Modes	Quadrature, Quadrature 4 edges, Direction Count, Forward, Backward
Synch In	Pulse Trig, Sequence Trig, Encoders
Synch Out	Pulse Trig, Sequence Trig, Output
Pin Assignments	Programmable
Number I/O	8

⁽¹⁾ The maximum data rate can vary according to the PC, the OS setting and the Software environment. ⁽²⁾ Measured at a 2 kHz PRF with a 5 MHz probe setting, all channels enabled. Photos and specifications not contractual.